

Product Introduction

FiberLink screening products are constructed of vinyl-coated fiberglass or polyester yarns. The screen is strong, long-lasting and is not easily damaged. Its main usage is for windows, doors, patio doors, patio enclosures and other outside structures to allow airflow but resist insects.

Product Description

The screening products that FiberLink provides include the following:

1. StarMesh (X1)

As the standard fiberglass insect screening, the main features of X1 are: corrosion resistant, good ventilation, high color stability, stable dimension, long-lasting, and easily cleaned. Fiberglass screen is available in a choice of several mesh sizes, widths and colors which can be customized upon request. Fiberglass screen is the material of choice for many builders in residential and commercial applications for its translucent appearance and low maintenance characteristics.

2. Patio Screen (X4)

The main features of X4 are: corrosion resistant, good ventilation, high color stability, stable dimension, long-lasting, and easily cleaned. X4 is available in a choice of several mesh sizes, widths and colors which can be customized upon request. Fiberglass screen is the material of choice for many builders in residential and commercial applications for its translucent appearance and low maintenance characteristics.

3. LiteMesh Screen (X5)

LiteMesh screen offers better visibility without compromising durability. In fact, you can enjoy up to 50% more natural light and dramatically improved airflow versus standard screening. The screening is easy to install while being durable and resistant to the elements. LiteMesh Screen helps filter sunlight and is ideal for applications including windows, doors, porches, gazebos and screen rooms.

4. Pet Screen (X6)

Pet Screen is an ultra-strong screening offering the optimal solution for tears and damage caused by household pets. This screening is much heavier than traditional fiberglass or aluminum screening, yet maintains its excellent outward visibility qualities. It can be easily installed anywhere the traditional screening is used, including windows, doors, porches, gazebos and screen rooms.

5. Aluminum Screen (X7)

Aluminum screen is strong and durable, rust resistant, and will not sag. Our screen made from this material offers good ventilation, protection from tiny bugs and high outward visibility for a crystal-clear view.

Packaging

Packaging is dependent on the width of screen required. All screens are packaged in plastic see through sheeting to allow at-a-glance product pulling.

For 600' rolls:

14" – 24" wide: 12 rolls per carton, 2 cartons per pallet

26" – 60" wide: 12 rolls per carton, 1 carton per pallet

72" or wider: 1 roll per carton, packed individually

For 100' rolls:

16" – 60" wide: 1 roll per box, 54 rolls (boxes) per pallet, or 70 rolls per carton, 1 or 2 cartons per pallet.

72" or wider: 1 roll per carton, packed individually

Storage

Unless otherwise specified, it is recommended to store the screening products in a cool, dry area. Temperature should not exceed 35°C (95°F) and the relative humidity should be kept below 75%. The products must remain in packaging material until just prior to their use. If these conditions are respected, the product should not undergo significant changes when stored for extended periods of time.

Stacking

To ensure safety and avoid damage to the product, skids should not be stacked more than three high.

Product Code	Unit	X1	X4	X5	X6	X7
Weave		Plain	Plain	Plain	Plain	Plain
Construction		18 x 36	18 x 24	20 x 20	15 x 11	18 x 16
Weight	g/m ²	115 ± 5	135 ± 5	75 ± 5	375 ± 25	200 ± 5
Warp	yarns/inch	18 ± 1	18 ± 1	20 ± 1	15 ± 1	18 ± 1
Weft	yarns/inch	16 ± 1	14 ± 1	20 ± 1	11 ± 1	16 ± 1
Standard Width	Inch	16 to 120	16 to 120	16 to 120	16 to 120	16 to 120
Length/Roll	Feet	100 & 600	100	100	100	100
Yarn Diameter	mm/inch	0.28 / 0.011	0.33 / 0.013	0.22 / 0.0087	0.60 / 0.0236	0.28 / 0.011
LOI	%	≥ 50	≥ 50	-	-	-
Break Strength (MD)	N	≥ 260	≥ 420	≥ 240	≥ 800	-
Break Strength (CD)	N	≥ 240	≥ 330	≥ 240	≥ 650	-
Glass Content	%	35	35	35	-	-
Polyester Content	%	-	-	-	30	-
Aluminum Alloy Content	%	-	-	-	-	100
PVC Content	%	65	65	65	70	-

* Choice of mesh sizes, widths, and colours available upon request.

Disclaimer of Liability

This data is offered solely as a guide in the selection of a reinforcement. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any liability arising out of its use or performance. The user, by accepting the products described herein, agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. It is important for the user to determine the properties of its own commercial compounds when using this or any other reinforcement. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this data sheet shall not be construed as representations of warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation.

